SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture CAS No. Mixture

Trade Name BERKEBILE MULTI-STATE INSTANT GUM CUTTER

Product Code B101-50

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)

Automotive care

Uses Advised Against None

Company Identification BERKEBILE OIL COMPANY

PO BOX 715 Somerset, PA 15501

Telephone (814) 443 -1656
Fax (814) 443 - 2873
E-Mail (competent person) info@berkebileoil.com

Emergency telephone number

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200) Flam. Aerosol 1; Compressed dissolved gas; Skin Irrit. 2; Eye Irrit. 2;

STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



Signal word(s)

Hazard Statement(s) Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Repeated exposure may cause skin dryness or cracking.

May cause drowsiness or dizziness.

Precautionary Statement(s) Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Avoid breathing spray.

Protect from sunlight and do not expose to temperatures exceeding 50

°C/122 °F.

Wash hands and exposed skin after use.

Keep out of reach of children.

Other hazards None

Revision: March 20, 2019 Page: 1/7

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	70 - 90	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Heptane, branched, cyclic and linear	5-15	426260-76-6	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336
Carbon dioxide	4 - 10	124-38-9	Compressed dissolved gas

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If symptoms develop, obtain

medical attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If symptoms

occur obtain medical attention.

Ingestion Do not give anything by mouth to an unconscious person. Seek medical

treatment.

Most important symptoms and effects, both acute and

delayed

May cause damage to organs: (Optic nerve, Central nervous system)

Indication of any immediate medical attention and

special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media

-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

Do not use water jet.

Special hazards arising from the substance or

mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

Revision: March 20, 2019 Page: 2/7

^{*} The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and Keep away from heat/sparks/open flames/hot surfaces. - No smoking. emergency procedures

Take precautionary measures against static discharges. Avoid contact

with skin and eyes. Avoid breathing vapors.

Environmental precautions Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections None **Additional Information** None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. - No

smoking. Avoid contact with skin and eyes. Use product in a well-

ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep in a cool, well ventilated place. Store at temperatures not

exceeding 50 °C / 122 °F.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s) Brake cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr TWA)		(STEL)		
		PEL	TLV	PEL	TLV	
SUBSTANCE.	CAS No.	(OSHA)	(ACGIH)	(OSHA)	(ACGIH)	Note:
Acetone	67-64-1	1000	500		750	^NIC
Heptane, branched, cylic and linear	426260-76-6	500 ppm*	1500 mg/m ³			*n-heptane
Carbon dioxide	124-38-9		5000 ppm		30,000 ppm	

[^]NIC = Notice of Intended Changes (ACGIH®);

Recommended monitoring method NIOSH 1300 (Ketones I); NIOSH 2000 (Methanol); NIOSH 1500

(hydrocarbons, B.P. 36 - 126 °C)

Exposure controls

Appropriate engineering controls Provide adequate ventilation to ensure that the occupational exposure

limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Revision: March 20, 2019 Page: 3/7

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required. Use gloves with insulation for thermal $% \left(1\right) =\left(1\right) \left(1\right$

protection, when needed.

Environmental Exposure Controls None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Liquid Color. Colorless Odor Acetone-like Odor Threshold (ppm) Not available pH (Value) Not available Melting Point (°C) / Freezing Point (°C) Not available Boiling point/boiling range (°C): 56 (Acetone) Flash Point (°C) -17 (Acetone)

Boiling point/boiling range (°C): 56 (Acetone)
Flash Point (°C) -17 (Acetone)
Evaporation Rate Not available
Flammability (solid, gas) Not applicable
Explosive Limit Ranges 2.5% - 12.8% v

Explosive Limit Ranges 2.5% - 12.8% v/v (Acetone) Vapor pressure (Pascal) 2.4 x 10⁴ (Acetone)

Vapor pressure (Pascal)

Vapor Density (Air=1)

Density (g/ml)

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

Auto Ignition Point (°C)

Auto (Pascal)

Not available

Not available

Not available

465 (Acetone)

Auto Ignition Point (°C) 465 (Acetone)

Decomposition Temperature (°C) Not available

Kinematic Viscosity <20

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Other information Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials Strong oxidizing agents

Hazardous decomposition product(s)

Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity Oral NOAEL = 900 mg/kg/day (rat) (90-days)

Inhalation NOAEL ≥ 19,000 ppm (rat)

It is unlikely to present a carcinogenic hazard to man.

Revision: March 20, 2019 Page: 4/7

Sensitization

Repeated dose toxicity

Negative

Carcinogenicity

Negative

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

Reproductive toxicity Oral: LD50 >5 g/kg-bw

Dermal: LD50 >2 g/kg-bw

Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Information on toxicological effects None known

Acetone (CAS No. 67-64-1)

Oral LD50 = 5800 mg/kg (rat) Acute toxicity

Dermal LD50 >15800 mg/kg (rabbit)

Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause

drowsiness and dizziness.

Irritation / Corrosivity Causes serious eye irritation. Repeated exposure may cause skin

dryness or cracking.

Sensitisation It is not a skin sensitiser.

Oral NOAEL = 900 mg/kg/day (rat) (90-days) Repeated dose toxicity

Inhalation NOAEL ≥ 19,000 ppm (rat)

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity Negative **Toxicity for reproduction** Negative Other information None known.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Substances in preparations / mixtures

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term LL50 (96 hour): >13.4 mg/L (Oncorhynchus mykiss)

EL50 (48 hour): 3 mg/l (Daphnia magna, mobility)

EC50 (96 hour): 13 mg/l (Pseudokirchnerella subcapitata)

NOELR (28 days) 1.5 mg/l (Fish) QSAR Long Term

LOEC (21 days): 0.32 mg/l (Daphnia magna)

NOEL (96 hour) 6.3 mg/l (Algae)

Persistence and degradability Readily biodegradable.

Bioaccumulative potential The product has no potential for bioaccumulation.

Mobility in soil Not available.

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

Page: 5/7 Revision: March 20, 2019

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	Sea transport <u>(IMDG)</u>	Air transport (ICAO/IATA)
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	70 - 90	5000

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
none		

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

	<u>'</u>		
Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None		

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: February 8,2019

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H225: Highly flammable liquid and vapor.
- H301: Toxic if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H311: Toxic in contact with skin.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H331: Toxic if inhaled.
- H336: May cause drowsiness or dizziness.
- H370: Causes damage to organs.

Revision: March 20, 2019 Page: 6/7

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Revision: March 20, 2019 Page: 7/7