SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: BERKEBILE OIL 2+2 CLEAN BRAKE (B-3501, B-3505, B-35055)

MANUFACTURED FOR: The Berkebile Oil Company INC. 1216 Red Brant Road Somerset, PA 15501 USA

Mailing Address: PO BOX 715 Somerset, PA 15501

EMERGENCY NUMBER: (800) 424-9300 (CHEM TREC)

INFO NUMBER: (814) 443-1656



CLASSIFICATION

Eye Damage/Irritation 2
Carcinogenicity 2
Aspiration hazard 2



SIGNAL WORD: Warning

Hazard Statements

May be harmful if swallowed and enters airways Suspected of causing cancer

Precautionary Statements

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wash hands thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Use personal protective equipment as required

Do NOT induce vomiting

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

IF exposed or concerned: Get medical advice/attention If eye irritation persists: Get medical advice/attention

Store locked up

Dispose of contents/container to comply with all local, state, and federal regulations

3. COMPOSITION/INFORMATION ON INGREDIENTS				
SDS for RERKERILE 2+2 CLEAN BRAKE R-3501 R3505 R-35055		Page 1 of 4		

Printed: 12/18/2015



Chemical Name CAS No. Percent

SDS for: BERKEBILE 2+2 CLEAN BRAKE B-3501, B3505, B-35055

	127-18-4	100.00
PERCHLOROETHYLENE	121-10-4	100.00

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breating has stopped. Get medical attention.

EYE CONTACT: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

INGESTION: If swallowed, do not induce vomiting. Get immediate medical attention.

Most important symptoms/effects, acute and delayed: Repeated exposure may cause skin dryness or cracking.

Indication of immediate medical attention and special treatment needed: None known.

5. FIRE FIGHTING MEASURES

Suitable and unsuitable extinguising media: Foam, Alcohol foam, CO2, Dry chemical, Water fog. Water spray may be ineffective.

Specific hazards arising from the chemical: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will not support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

Special equipment and precautions for fire-fighters: Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

Methods and materials for containment and cleaning up: Clean up with absorbent material and place in closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep closure tight and container upright to prevent leakage. Open container slowly. Do not get in eyes. Avoid skin contacct and contact with clothing. Do not take internally.

Conditions for safe storage, including any incompatibilities: Store and use in cool, dry, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat or open flame.

8. EXPOSURE CONTROL/PERSONAL PROTECTION				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	

PERCHLOROETHYLENE	Short term value: C 200; 300	Short term value: 685	
127-18-4	ppm	mg/m3, 100 ppm	
	Long term value: 100 ppm	Long term value: 170	
		mg/m3; 25 ppm	

Appropriate engineering controls: Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhoust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lel below stated limit.

Individual protection measures:

Respiratory protection: None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination or particles and vapor. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Protective gloves: None under normal use. Use solvent-resistant for prolonged or repeated contact.

Eye protection: None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

Other protective clothing or equipment: None under normal use. However, use of solvent- resitant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid

Vapor Pressure: Not determined

Vapor Density: Heavier than air

Density: 1.611585317

Freezing point: Not determined

Boiling point: 121°C

Evaporation rate: Slower than ether

Explosive Limits: Not applicable

Autoignition temperature: Not determined

Viscosity: Not determined

Odor: Chlorinated solvent

Odor threshold: Not determined

pH: Not applicable

Melting point: Not determined

Solubility: Not determined

Flash point: Not determined

Flammability: None

Partition coefficient (n- Not determined

octanol/water):

Decomposition temperature: Not determined

10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal storage and handling conditions.

Possibility of hazardous reactions: None known.

Incompatible materials: Strong oxidizing agents.

Acids, Bases, Strong oxidizing agents, Oxygen, Peroxides, Reactive metals, Aluminum

SDS for: BERKEBILE 2+2 CLEAN BRAKE B-3501, B3505, B-35055

Hazardous decomposition products:

Hydrogen chloride, chlorine, phosgene, oxides of carbon

11. TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

12. ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

14. TRANSPORT INFORMATION

By land: UN1897 Tetrachloroethylene, 6.1, III.

By water: UN1897 Tetrachloroethylene, 6.1, III.

By air: UN1897 Tetrachloroethylene, 6.1, III.

15. REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

16. OTHER INFORMATION

Date Prepared: 4/20/2015 Revision 0

Date revised: 2015-04-20

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.

SDS for: BERKEBILE 2+2 CLEAN BRAKE B-3501, B3505, B-35055

Page 6 of 4