

SAFETY DATA SHEET

This document is not intended for general distribution.

It can be used as the basis for a general distribution document if appropriate changes are made to the identification section.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: **RED GREASE B-3600**

Product Code: 2902009

Manufacturer Name The Berkebile Oil Company

Address 1216 Red Brant Road
Somerset, PA 15501, PO BOX 715

Phone 814-443-1656

Email info@berkebileoil.com

Fax 814-443-2873

Chemtrec Emergency Tel # 800-424-9300

Product Use: Special purpose lubrication

2. HAZARDS IDENTIFICATION

CLASSIFICATION

Flammable aerosol

1

Gas under pressure

Liquefied gas

Skin Corrosion/Irritation

4

Eye Damage/Irritation

2B

Danger

SIGNAL WORD:

Hazard Statements

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Causes eye irritation

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking

Do not spray on an open flame or other ignition source

Pressurized container – Do not pierce or burn, even after use

Wash hands thoroughly after handling

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

If eye irritation persists: Get medical advice/attention

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with all local, state, and federal regulations

3. COMPOSITION/INFORMATION ON INGREDIENTS

| | Chemical Name | CAS No. | Percent |
|---|----------------------|----------------|----------------|
| 64742-52-5 | | | 37.00 |
| PETROLEUM OIL | | | |
| 64742-49-0 | | | 24.60 |
| NAPHTHA (PETROLEUM), HYDROTREATED LIGHT | | | |
| 74-98-6 | | | 12.70 |
| PROPANE | | | |
| SDS for: 2902009 | | | |

BUTANE
112945-52-5

SILICON DIOXIDE, CRYSTALLINE-FREE

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

EYE CONTACT: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

INGESTION: Not a likely route of exposure.

Most important symptoms/effects, acute and delayed: Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed: None known.

5. FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media: Foam, Alcohol foam, CO2, Dry chemical, Water fog. Water spray may be ineffective.

Specific hazards arising from the chemical: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

Special equipment and precautions for fire-fighters: Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

Methods and materials for containment and cleaning up: Clean up with absorbent material and place in closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

Conditions for safe storage, including any incompatibilities: Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Other Exposure Limits

**ACGIH Exposure Limits
OSHA Exposure Limits
Chemical Name / CAS No.**

PEL: Mist 5 mg/m3, 8 hrs
TLV: Mist 5 mg/m3, 8 hrs
PETROLEUM OIL
64742-52-5
SDS for: 2902009

TWA: 500 ppm;
PEL-CEILING: not determined
TLV-TWA: 400 ppm
TLV-STEL: 500 ppm
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
64742-49-0
Not established
TWA: 1000 ppm
PROPANE
74-98-6
Not established
TWA: 1000 ppm
BUTANE
106-97-8
Not established
Not established
SILICON DIOXIDE, CRYSTALLINE-FREE
112945-52-5

Appropriate engineering controls: Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhaust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lcl below stated limit.

Individual protection measures:

Respiratory protection: None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Protective gloves: None under normal use. Use solvent-resistant for prolonged or repeated contact.

Eye protection: None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

Other protective clothing or equipment: None under normal use. However, use of solvent-resistant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Aerosol product

Odor:Solvent

Vapor Pressure:Not determined

Odor threshold:Not determined

Vapor Density:Heavier than air

pH:Not applicable

Density:0.720363515

Melting point:Not determined

Freezing point:Not determined

Solubility:Not determined

Boiling point:93°C

Flash point:Not determined

Evaporation rate:Slower than ether

Flammability:Level 3 Aerosol

Explosive Limits:Not applicable

Partition coefficient (n-octanol/water):Not determined

Autoignition temperature:Not determined

Decomposition temperature:Not determined

Viscosity:Not determined

10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal storage and handling conditions.

Possibility of hazardous reactions: None known.

Incompatible materials:

No data

Hazardous decomposition products:

No data

11. TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

12. ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

14. TRANSPORT INFORMATION

By land: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Lubricant, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

By air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

15. REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

16. OTHER INFORMATION

Revision 0

Date revised: 2015-06-02

Date Printed: 2015-06-01

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.

SDS for: 2902009

Page 4 of 4

Printed: 6/1/2015